

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

1 Identification

Product identifier

Trade name:
Osmo Oil Stain
Article number:

3501, 3512, 3514, 3516, 3518, 3519, 3541, 3543, 3564, 3590

Application of the substance / the mixture

 Priming
 Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

 Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf
 Germany

Information department:

 Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

Emergency telephone number:

 24h-Emergency Phone Number:
 For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or Night
 within USA and Canada 1-800-424-9300
 Outside USA and Canada 001-703-527-3887 (WISAG FMO cargo Services GmbH & Co.KG)

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

Carc. 2 H351 Suspected of causing cancer.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms


GHS08

Signal word

Warning

Hazard-determining components of labeling:

 titanium dioxide
 H227 Combustible liquid.

Hazard statements

H351 Suspected of causing cancer.

Precautionary statements

 P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from flames and hot surfaces. – No smoking.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves / eye protection.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.

Classification system:

NFPA ratings (scale 0 - 4) Health = 0

Fire = 2

Reactivity = 0

HMIS-ratings (scale 0 - 4) Health = 0

Fire = 2

Reactivity = 0

Other hazards CAUTION: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

Results of PBT and vPvB assessment

PBT: Not applicable.



vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-48-9	aliphatic hydrocarbons, C10-C13	 Asp. Tox. 1, H304; Flam. Liq. 4, H227	25-50%
13463-67-7	titanium dioxide	 Carc. 2, H351	10-25%

Additional information: The content of Titanium dioxide varies according to the colour shade.
 The content of Titanium dioxide varies according to the colour shade. 3516, 3519, 3541, 3543, 3564, 3590 are complete without Titanium dioxide.

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.
 Take affected persons out into the fresh air.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 2)

After skin contact:	Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
Information for doctor:	
Most important symptoms and effects, both acute and delayed	Dizziness Headache
Indication of any immediate medical attention and special treatment needed	No further relevant information available.

5 Fire-fighting measures

Extinguishing media	
Suitable extinguishing agents:	CO ₂ , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents:	Water with full jet
Special hazards arising from the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
Advice for firefighters	
Protective equipment:	Mouth respiratory protective device.
Additional information	Cool endangered receptacles with water spray. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	
	Ensure adequate ventilation Keep away from ignition sources
Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up:	
	Warm water and cleansing agent Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Reference to other sections	
	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 3)

Protective Action Criteria for Chemicals**PAC-1:**

13463-67-7	titanium dioxide	30 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

PAC-2:

13463-67-7	titanium dioxide	330 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³

PAC-3:

13463-67-7	titanium dioxide	2,000 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

7 Handling and storage**Handling:****Precautions for safe handling**

Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Keep receptacle tightly sealed.

Storage class:

10

Specific end use(s)

No further relevant information available.

(Contd. on page 5)

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 4)

8 Exposure controls/personal protection

Additional information about design of technical systems:

No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Short term filter device:

Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 ° C)).

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

To avoid skin problems reduce the wearing of gloves to the required minimum.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Goggles recommended during refilling.

Body protection:

Protective work clothing

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 5)

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Viscous
Color:	Different according to coloring
Odor:	Mild

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 180 °C (>356 °F)

Flash point: > 60 °C (>140 °F) (DIN 53213)**Ignition temperature:** 240 °C (464 °F)**Auto igniting:** Product is not selfigniting.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.**Explosion limits:**

Lower:	0.7 Vol %
Upper:	6.0 Vol %

Density at 20 °C (68 °F): 0.90 - 1.15 g/cm³ (7.511-9.597 lbs/gal) (DIN 51757)**Solubility in / Miscibility with****Water:** Not miscible or difficult to mix.**Viscosity:**

Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	30-45 s (DIN 53211/4 mm)

Solvent content:

VOC content:	< 450 g/l / < 3.7 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity**Reactivity** No further relevant information available.**Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

Possibility of hazardous reactions Reacts with fabric soaked in the product (e.g. cleaning wool).**Conditions to avoid** No further relevant information available.**Incompatible materials:** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 6)

Hazardous decomposition products:

Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)

Additional information:

CAUTION: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

Primary irritant effect:

on the skin:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

Irritating effect.

Sensitization:

Sensitizing effect by skin contact is possible with prolonged exposure.

Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

13463-67-7	titanium dioxide	2B
14808-60-7	Quartz (SiO ₂)	1

NTP (National Toxicology Program)

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 7)

12 Ecological information**Toxicity****Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	>1,000 mg/l (daphnia) (OECD 202)
EC50/ 72h	>1,000 mg/l (algae) (OECD 201)
LC50 / 96h	>1,000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	% (leicht abbaubar)

Persistence and degradability No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.**13 Disposal considerations****Waste treatment methods****Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**Uncleaned packagings:****Recommendation:** Disposal must be made according to official regulations.**14 Transport information****UN-Number****DOT, ADR, ADN, IMDG, IATA** Void**UN proper shipping name****DOT, ADR, ADN, IMDG, IATA** Void**Transport hazard class(es)****DOT, ADR, ADN, IMDG, IATA****Class** Void

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 8)

Packing group <i>DOT, ADR, IMDG, IATA</i>	Void
Environmental hazards: <i>Marine pollutant:</i>	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65**Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO₂)**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenicity categories**EPA (Environmental Protection Agency)**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 9)

<i>TLV (Threshold Limit Value established by ACGIH)</i>		
13463-67-7	titanium dioxide	A4
14808-60-7	Quartz (SiO ₂)	A2

<i>NIOSH-Ca (National Institute for Occupational Safety and Health)</i>		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO ₂)	

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

GHS08

Signal word

Warning

Hazard-determining components of labeling:

titanium dioxide

Hazard statements

H227 Combustible liquid.

H351 Suspected of causing cancer.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from flames and hot surfaces. – No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Date of preparation / last revision 06/26/2018 / 1

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/26/2018

Reviewed on 06/26/2018

Trade name: Osmo Oil Stain

(Contd. of page 10)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Carc. 2: Carcinogenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

*** Data compared to the previous
version altered.**